

## S-26 BUCCANEER LIQUID PLASTICS

### 2.1 S-26 Brick Seal

SOLVENT SOLUBLE – with Voc's

#### General application instructions

S-26 Brick Seal is a clear non yellowing plastic, that can be applied to vertical and horizontal surfaces i.e. face brick walls or concrete floors.

It is fully 100% water proof and can tolerate very heavy traffic. It is a seamless coating and can be taken up from floors to walls. It is very quick drying. It fully water proofs brick work, stone or terrazzo and porous flat surfaces.

**S-26 Brick Seal can be used as a Liquid Tiling – Plastic Wall Coating, see 2.4 for instruction.**

▶ NEVER DILUTE THE PRODUCT!

#### Application Instruction:

**Important: See our Preliminary and General (P&G) Notes**

Allow plenty of ventilation in confined areas and spaces and never allow ignition, smoking or naked flame when application is taking place. An industrial fan will increase air circulation and will assist in the product drying and curing.

Always apply 2 full coats of S-26 Brick Seal..

Never apply onto a wet or damp surface. Ensure that the substrata is below a 3% moisture content.

Always ensure that no rising damp can occur on flat surfaces.

An industrial fan will increase air circulation and will assist in the product drying and curing.

<b>Application Tools:</b>	Brush, Roller, Spray Method
<b>Cleaning Tools With:</b>	Xylene
<b>Spread Rate:</b>	±6m <sup>2</sup> per litre depending on substrata
<b>Packaging:</b>	1L, 5L, 20L
<b>Colour:</b>	Clear