

S-26 BUCCANEER LIQUID PLASTICS

1.4 S-26 Plastic Crack Filler

WATER SOLUBLE – No Voc's

General application instructions

S-26 Plastic Crack Filler is a true long lasting and very effective crack filling mastic that can be adapted to most, if not all types of crack filling operations onto virtually any surface and building.

Unlike most powdered crack fillers that crack again after application, S-26 Plastic Crack Filler, if applied correctly will not do this.

Application Instruction:

Important: See our Preliminary and General (P&G) Notes

- To apply into normal fine hairline cracks simply use a spatula and push the product into the crack and leave a smooth finish. Sand paper where necessary.
- To apply into large or deep cracks, first open the crack and then prime using the S-26 Stabilizing Primer and allow to dry. Then fill the crack using S-26 Plastic Crack Filler.

Adding Cement: A small proportion of cement 5% to 10% can be added to the S-26 Plastic Crack Filler. The more cement that is added the less flexible the S-26 Plastic Crack Filler will become. On buildings that have a pastel finish, only use white cement. Never dilute.

To obtain a stipple finish to match an existing stipple plaster, simply use a stipple roller to finish off.

The end result is a fully 100% water proof crack.

Application Tools:	Spatula
Cleaning Tools With:	Water
Spread Rate:	n/a
Packaging:	1L, 5L
Colour:	Off-White